

Safety Data Sheet

according to the WHS Regulations Issue date: 4/12/2023 Date of revision: 4/12/2023 Supersedes: 29/03/2023 Version: 1.4

SECTION 1: Product identifier	
1.1. GHS Product identifier	
	A lnk Red 12020 12030
1.2. Other means of identification	
Synonyms :	Marking Pen ink for marking porous surfaces.
1.3. Recommended use of the chemical and re	estrictions on use
	M10 Marking Pen Ink Not to be used for any purpose other than the one the product was designed for
1.4. Details of manufacturer or importer	
Signet Pty Ltd 56 Ingleston Rd WAKERLEY, QLD 4154 Australia T +61 (07) 3179 2100 sales@signet.net.au - www.signet.net.au	
1.5. Emergency phone number	
Emergency number :	Office hours: +61 (07) 3179 2100 Poisons Information Centre (24 h): 13 11 26
SECTION 2: Hazard identification 2.1. Classification of the hazardous chemical	
Classification according to the model Work Health a	and Safety Regulations (WHS Regulations)
Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2A	H315 H319
Carcinogenicity, Category 1B	H350
Specific target organ toxicity - Single exposure, Catego	•
Specific target organ toxicity – Single exposure, Catego tract irritation	ory 3, Respiratory H335
Specific target organ toxicity – Repeated exposure, Cat	egory 1 H372
Aspiration hazard, Category 1	H304
2.2. GHS Label elements, including precaution	nary statements
Hazard pictograms (GHS AU) :	Flame Exclamation Health hazard
Signal word (GHS AU) :	mark Danger
Contains :	xylene (30 – 60 %); Mineral Turpentine (30 – 60 %)

4/12/2023 (Date of revision)

: H226 - Flammable liquid and vapour

H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness

H304 - May be fatal if swallowed and enters airways

Safety Data Sheet

according to the WHS Regulations

	H350 - May cause cancer
	H372 - Causes damage to organs through prolonged or repeated exposure
Precautionary statements (GHS AU)	: P101 - If medical advice is needed, have product container or label at hand.
	P102 - Keep out of reach of children.
	P103 - Read carefully and follow all instructions.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
	P240 - Ground and bond container and receiving equipment.
	P241 - Use explosion-proof equipment.
	P260 - Do not breathe vapours.
	P264 - Wash hands thoroughly after handling.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients		
Name	CAS-No.	%
xylene	1330-20-7	30 – 60
Mineral Turpentine	-	30 – 60

SECTION 4: First aid measures

4.1. Description of necessary first-aid	measures
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	 Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	 Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a physician immediately. Do not induce vomiting.
4.2. Symptoms caused by exposure	
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Irritation. : Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.
4.3. Medical attention and special trea	itment

Other medical advice or treatment

: Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Unsuitable extinguishing media are not known.	
5.2. Specific hazards arising from the chemi	ical	
Fire hazard General measures Hazardous decomposition products in case of fire	 Flammable liquid and vapour. No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters. Toxic fumes may be released. 	

Safety Data Sheet

according to the WHS Regulations

5.3. Special protective equipment and precautions for fire-fighters		
Firefighting instructions	: Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location.	
Protection during firefighting	 Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 	
Hazchem Code	: * 3Y	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipm	ent and emergency procedures	
General measures :	No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.	
6.1.1. For non-emergency personnel		
Emergency procedures :	No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.	
6.1.2. For emergency responders		
Protective equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up	
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includin	g any incompatibilities
Technical measures Storage conditions Information on mixed storage	 Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
Storage area Special rules on packaging	 Keep out of direct sunlight. Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage.
Packaging materials	: Keep only in original packaging.

Safety Data Sheet

according to the WHS Regulations

SECTION 8: Exposure controls and personal protection	
8.1. Control parameters - exposure star	ndards
No additional information available	
8.2. Monitoring methods	
Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when toxic gases may be released. Gas detectors should be used when flammable gases/vapours may be released.
8.3. Engineering controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system.
8.4. Individual protection measures, such	ch as personal protective equipment (PPE)
Personal protective equipment	 Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves: Antistatic gloves
Eye protection	: Wear eye protection: Chemical goggles or safety glasses. eye protection (EN166)
Skin and body protection	: Wear foot protection: antistatic boots. Wear protective clothing: Antistatic clothing, Flame retardant protective clothing. Use protective apron: Chemical resistant apron
Respiratory protection	: Wear appropriate mask: Combined gas/dust mask with filter type
Personal protective equipment symbol(s)	
Consumer exposure controls Other information	 Personal protective equipment (PPE) is not required when handling individual retail pack. PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Red
Odour	: characteristic
Odour threshold	: No data available
рН	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not applicable
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: ≈ 0.856 kg/l
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 8.178 mm²/s
Viscosity, dynamic	: < 7 cP

Safety Data Sheet

according to the WHS Regulations

Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
Fat solubility	: No data available

SECTION 10: Stability and reactive	vity
Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	 Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
Acute toxicity (dermal) :	Not classified Not classified Not classified	
xylene (1330-20-7)		
LD50 oral	4300 mg/kg bodyweight	
LD50 dermal	> 5000 mg/kg bodyweight	
LC50 Inhalation - Rat (Dust/Mist)	> 10000 mg/l	
Serious eye damage/irritation:Respiratory or skin sensitisation:Germ cell mutagenicity:Carcinogenicity:Reproductive toxicity:	Causes skin irritation. Causes serious eye irritation. Not classified Not classified May cause cancer. Not classified May cause drowsiness or dizziness. May cause respiratory irritation.	
xylene (1330-20-7)		
STOT-single exposure	May cause respiratory irritation.	
Mineral Turpentine		
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.	
STOT-repeated exposure :	Causes damage to organs through prolonged or repeated exposure.	
xylene (1330-20-7)		
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90- Day Oral Toxicity)	
Mineral Turpentine		
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard :	May be fatal if swallowed and enters airways.	
A Ink Red		
Viscosity, kinematic	8.178 mm²/s	
xylene (1330-20-7)		
Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
Animal studies and expert judgment for classification	False	

Safety Data Sheet

according to the WHS Regulations

Mineral Turpentine	
Animal studies and expert judgment for classification	False
Viscosity, kinematic	1.227 mm²/s

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

40.4 Exclusion	
12.1. Ecotoxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long–term (chronic)	: Not classified
xylene (1330-20-7)	
EC50 - Other aquatic organisms [1]	350 mg/l waterflea
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Ozone	: Not classified
Other adverse effects	: No additional information available
A Ink Red	
Fluorinated greenhouse gases	False
xylene (1330-20-7)	
Fluorinated greenhouse gases	False
Mineral Turpentine	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations	
Waste treatment methods Additional information	Dispose of contents/container in accordance with licensed collector's sorting instructions.Flammable vapours may accumulate in the container.

Safety Data Sheet

according to the WHS Regulations

ADG	IMDG	ΙΑΤΑ
14.1. UN number		
1210	1210	1210
14.2. UN Proper Shipping Name		
PRINTING INK	PRINTING INK	Printing ink
14.3. Transport hazard class(es)		5
3	3	3
		·
14.4. Packing group		
III - Substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
4.6. Special precautions for user		
pecific storage requirement hock sensitivity	: No data available : No data available	
4.7. Additional information		
Other information	: No supplementary information available	
ransport by road and rail		
IN-No. (ADG)	: 1210	
pecial provision (ADG) imited quantities (ADG)	: 163, 223, 367 : 5l	
Excepted quantities (ADG)	: 51 : E1	
vacking instructions (ADG)	2 E I 2 P001, IBC03, LP01	
pecial packing provisions (ADG)	: PP1	
ortable tank and bulk container instructions (ADG)		
Portable tank and bulk container instructions (ADG)		
ADG)		
ransport by sea		
IN-No. (IMDG)	: 1210	
pecial provisions (IMDG)	: 163, 223, 367, 955	
imited quantities (IMDG)	: 5L	
excepted quantities (IMDG)	: E1	
Packing instructions (IMDG)	: P001, LP01	
pecial packing provisions (IMDG)	: PP1	
3C packing instructions (IMDG)	: IBC03	
ank instructions (IMDG)	: T2	
ank special provisions (IMDG)	: TP1 : F-E - FIRE SCHEDULE Echo - NON-WATE	
:mS-No. (Fire) :mS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAM	
itowage category (IMDG)	: S-D - SPILLAGE SCHEDULE Della - FLAN : A	
Properties and observations (IMDG)	: Fluid or viscous liquid containing colouring	matter in solution or suspension. Miscibility wi
	water depends upon the solvent.	
.ir transport	water depends upon the solvent.	

Safety Data Sheet

according to the WHS Regulations

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code

: * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All the chemicals contained in this product are listed introductions

Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Routine Review - No significant changes from previous issue.

Data sources

	Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals
	Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals
	Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants
	Safe Work Australia - Hazardous Chemical Information System (HCIS)
	Australian Inventory of Industrial Chemicals (AICIS Inventory)
	Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice
	2020
	Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017
	Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017
	New Zealand - Chemical Classification and Information Database (CCID)
	New Zealand - Inventory of Chemicals (NZIoC)
	European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)
	European Chemicals Agency (ECHA) - REACH Study Results
	European Chemicals Agency (ECHA) - REACH Registration Dossiers
	United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
	Uniform Scheduling of Medicines and Poisons (SUSMP)
	United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)
	Australian Dangerous Goods Code (ADG Code)
	International Air Transport Association Dangerous Goods Regulations (IATA DGR)
	International Maritime Dangerous Goods (IMDG Code).
n :	4/12/2023
on	
	H226

Date of revisio

Classification

Safety Data Sheet

according to the WHS Regulations

Classification		
Skin Irrit. 2	H315	
Eye Irrit. 2A	H319	
Carc. 1B	H350	
STOT SE 3	H336	
STOT SE 3	H335	
STOT RE 1	H372	
Asp. Tox. 1	H304	

Full text of H-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.