

Safety Data Sheet

according to the WHS Regulations Issue date: 14/02/2023 Version: 1.0

SECTION 1: Product identifier	
1.1. GHS Product identifier	
Product form Product name Product code	: Mixture : DO Ink- Yellow : 12195
1.2. Other means of identification	
No additional information available	
1.3. Recommended use of the chemical an	id restrictions on use
Recommended use	 DO inks are a high viscosity permanent ink for marking almost any surface through ball markers. Not to be used for any purpose other than the one the product was designed for
1.4. Details of manufacturer or importer	
Supplier Signet Pty Ltd 56 Ingleston Rd WAKERLEY, QLD 4154 Australia T +61 (07) 3179 2100 sales@signet.net.au - www.signet.net.au	
1.5. Emergency phone number	
Emergency number	: Office hours: +61 (07) 3179 2100 Poisons Information Centre (24 h): 13 11 26
SECTION 2: Hazard identification	
2.1. Classification of the hazardous chemi	cal
Classification according to the model Work Hea	Ith and Safety Regulations (WHS Regulations)
Flammable liquids, Category 3 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2A Specific target organ toxicity – Repeated exposure,	H226 H315 H319 Category 2 H373
2.2. GHS Label elements, including precau	itionary statements
Hazard pictograms (GHS AU)	Flame Exclamation Health hazard mark
Signal word (GHS AU) Contains Hazard statements (GHS AU)	 Warning ethylene glycol monobutyl ether (10 – 30 %) H226 - Flammable liquid and vapour H315 - Causes skin irritation

- H315 Causes skin irritation
- H319 Causes serious eye irritation

H373 - May cause damage to organs through prolonged or repeated exposure

- : P101 If medical advice is needed, have product container or label at hand.
 - P102 Keep out of reach of children.
 - P103 Read carefully and follow all instructions.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Precautionary statements (GHS AU)

Safety Data Sheet

according to the WHS Regulations

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Ethanol	64-17-5	30 - 60
ethylene glycol monobutyl ether	111-76-2	10 – 30

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures		
First-aid measures general	: Get medical advice/attention if you feel unwell.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.	
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.	
First-aid measures after eye contact	: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.	
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.	
4.2. Symptoms caused by exposure		
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Irritation. : Eye irritation.	
4.3. Medical attention and special treatme	ent	
Other medical advice or treatment	: Treat symptomatically.	

SECTION 5: Fire-fighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Unsuitable extinguishing media are not known.	
5.2. Specific hazards arising from the chem	ical	
Fire hazard General measures Hazardous decomposition products in case of fire	 Flammable liquid and vapour. No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters. Toxic fumes may be released. 	
5.3. Special protective equipment and preca	autions for fire-fighters	
Firefighting instructions Protection during firefighting Hazchem Code	 Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. * 3Y 	

Safety Data Sheet

according to the WHS Regulations

SECTION 6: Accidental release measures		
6.1. Personal precautions, prote	ective equipment and emergency procedures	
General measures	: No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.	
6.1.1. For non-emergency personnel		
Emergency procedures	 Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. 	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3 Methods and materials for containment and cleaning up		

sion motione and materiale for containment and cloaning up		
Methods for cleaning up	:	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 	
7.2. Conditions for safe storage, in	cluding any incompatibilities	
Technical measures Storage conditions Information on mixed storage	 Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. 	
Storage area Special rules on packaging	 Keep out of direct sunlight. Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage. 	
Packaging materials	: Keep only in original packaging.	

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethanol (64-17-5)	
Australia - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
OES TWA [1]	1880 mg/m³
OES TWA [2]	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Safety Data Sheet

according to the WHS Regulations

Australia - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl cellosolve; Butyl glycol; Ethylene glycol monobutyl ether; Glycol monobutyl ether)
OES TWA [1]	96.9 mg/m ³
OES TWA [2]	20 ppm
OES STEL	242 mg/m ³
OES STEL [ppm]	50 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
8.2. Monitoring methods	
Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.
8.3. Engineering controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment.
8.4. Individual protection measures, such	as personal protective equipment (PPE)
Personal protective equipment	: Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves: Antistatic gloves
Eye protection	: Wear eye protection: Chemical goggles or safety glasses
Skin and body protection	: Wear foot protection: antistatic boots. Wear protective clothing: Antistatic clothing, Flame retardant protective clothing
Respiratory protection	: Use half mask to protect the face from liquid splashes
Personal protective equipment symbol(s)	

Consumer exposure controls Other information Personal protective equipment (PPE) is not required when handling individual retail pack.
 PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS210.

Physical state	: Liquid
Appearance	: No data available
Molecular mass	: Not applicable
Colour	: Yellow
Odour	: Not available
Odour threshold	: No data available
pH	: Not available
pH solution	: Not available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not available
Boiling point	: 78 – 170 °C

Safety Data Sheet

according to the WHS Regulations

: 24 °C
: Not available
: Not available
: No data available
: Vapour pressure: 1 – 5 kPa
: Relative vapour density at 20°C: Not available. (Air=1).
: Density: ≈ 0.9 kg/l
Relative density: (Water = 1).
: No data available
: Not available
: Not available
: No data available
: No data available
: No data available
: Not available
: No data available

SECTION 10: Stability and reactivity	
Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	 Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified : Not classified
Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg Source: ECHA
ethylene glycol monobutyl ether (111-76-2)	
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg Source: ECHA
Skin corrosion/irritation	Causes skin irritation. pH: Not available
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not available
Respiratory or skin sensitisation	Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:

Safety Data Sheet

according to the WHS Regulations

ethylene glycol monobutyl ether (111-76-2)		
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard : Not classified		
DO Ink- Yellow		
Viscosity, kinematic	Not available	
Ethanol (64-17-5)		
Animal studies and expert judgment for classification	False	
Viscosity, kinematic	1.366 mm²/s	
ethylene glycol monobutyl ether (111-76-2)		
Animal studies and expert judgment for classification	False	

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity	
Hazardous to the aquatic environment, short-term : (acute)	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Not classified Not classified
Ethanol (64-17-5)	
LC50 - Fish [1]	> 100 mg/l Source: SIDS 2005
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
ErC50 algae	275 mg/l Source: ECHA
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC
ethylene glycol monobutyl ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l Source: ECHA
EC50 - Crustacea [1]	1800 mg/l Source: ECHA
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential	
DO Ink- Yellow	
Partition coefficient n-octanol/water (Log Pow)	Not available
Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC

Safety Data Sheet

according to the WHS Regulations

0.81 Source: ECHA	
Not available	
-0.32 Source: ICSC	
0.81 Source: ECHA	
Not classified	
No additional information available	
False	
False	
ethylene glycol monobutyl ether (111-76-2)	
False	

SECTION 13: Disposal considerations	
Waste treatment methods Additional information	 Dispose of contents/container in accordance with licensed collector's sorting instructions. Flammable vapours may accumulate in the container.

SECTION 14: Transport information

ADG	IMDG	ΙΑΤΑ
14.1. UN number		
1210	1210	1210
14.2. UN Proper Shipping Name		1
PRINTING INK	PRINTING INK	Printing ink
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		1
III - Substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

Safety Data Sheet

according to the WHS Regulations

Specific storage requirement	: No data available
Shock sensitivity	: No data available
14.7. Additional information	
Other information	: No supplementary information available
Transport by road and rail	. 4040
UN-No. (ADG)	: 1210
Special provision (ADG)	: 163, 223, 367
Limited quantities (ADG)	: 5l : E1
Excepted quantities (ADG)	
Packing instructions (ADG)	: P001, IBC03, LP01
Special packing provisions (ADG)	: PP1
Portable tank and bulk container instructions (ADG)	
	: TP1
(ADG)	
Transport by sea	
UN-No. (IMDG)	: 1210
Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Fluid or viscous liquid containing colouring matter in solution or suspension. Miscibility wit water depends upon the solvent.
Air transport UN-No. (IATA)	: 1210
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L
14.8. Hazchem or Emergency Action Code	
Hazchem Code	: * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : Listed Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

Safety Data Sheet

according to the WHS Regulations

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

Data sources

: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants Safe Work Australia - Hazardous Chemical Information System (HCIS) Australian Inventory of Industrial Chemicals (AICIS Inventory) Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020 Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017 Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017 New Zealand - Chemical Classification and Information Database (CCID) New Zealand - Inventory of Chemicals (NZIoC) European Chemicals Agency (ECHA) - Annex VI (C&L Inventory) European Chemicals Agency (ECHA) - REACH Study Results European Chemicals Agency (ECHA) - REACH Registration Dossiers United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS) Uniform Scheduling of Medicines and Poisons (SUSMP)

United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation) Australian Dangerous Goods Code (ADG Code)

International Air Transport Association Dangerous Goods Regulations (IATA DGR) International Maritime Dangerous Goods (IMDG Code).

Classification	
Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT RE 2	H373

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. 5 (Dermal)	Acute toxicity (dermal), Category 5
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Liq. 4	Flammable liquids, Category 4
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H225	Highly flammable liquid and vapour

Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.