

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : Colour Code (Various Colours) - Aerosol Paints  
Product code : 11701 11702 11703 11704 11705 11706 11707 11708 11709 11710 11711 11712 11713  
11714 11715 11716 11717 11718 11719 11720 11721 11724

#### 1.2. Other means of identification

Synonyms : Colour Code Signal Red; 11702 Colour Code Pink; 11703 Colour Code Red gum; 11704 Colour Code marigold; 11705 Colour Code warm white; 11706 Colour Code biscuit; 11707 Colour Code golden tan; 11708 Colour Code sunflower; 11709 Colour Code custard; 11710 Colour Code violet; 11711 Colour Code lilac; 11712 Colour Code bluebell; 11713 Colour Code dark grey blue; 11714 Colour Code turquoise; 11715 Colour Code bottle green; 11716 Colour Code jade; 11717 Colour Code serpentine; 11718 Colour Code black; 11719 Colour Code white; 11720 Colour Code light blue; 11721 Colour Code lime green; 11724 Colour Code Megenta; Aerosol paint, spray can paint.

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Fast drying spray for cheap effective stencilling on any surface. Bright light fast colours. Application is by spray atomisation from a hand held aerosol pack.  
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.4. Details of manufacturer or importer

##### Supplier

Signet Pty Ltd  
56 Ingleston Rd  
WAKERLEY, QLD 4154  
Australia  
T +61 (07) 3179 2100  
[sales@signet.net.au](mailto:sales@signet.net.au) - [www.signet.net.au](http://www.signet.net.au)

#### 1.5. Emergency phone number

Emergency number : Office hours: +61 (07) 3179 2100  
Poisons Information Centre (24 h): 13 11 26

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Acute Hazard, Category 3	H402
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

Signal word (GHS AU)	: Danger
Contains	: Ethyl Acetate (10 – 60 %); Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (< 10 %); Solvent naphtha (petroleum), light aromatic [contains less than 0,1 % w/w benzene] (< 10 %)
Hazard statements (GHS AU)	: H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS AU)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves.
Additional hazard statements (GHS AU)	: AUH066 - Repeated exposure may cause skin dryness or cracking. AUH044 - Risk of explosion if heated under confinement.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Ethyl Acetate	141-78-6	10 – 60
Ethanol	64-17-5	< 30
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).]	64742-82-1	< 10

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Unsuitable extinguishing media are not known.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and materials for containment and cleaning up

- For containment : Collect spillage.  
Methods for cleaning up : Mechanically recover the product.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Does not require any specific or particular technical measures.  
Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

Information on mixed storage	: Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
Storage area	: Keep out of direct sunlight.
Special rules on packaging	: Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage.
Packaging materials	: Keep only in original packaging.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

Ethanol (64-17-5)	
Australia - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
OES TWA [1]	1880 mg/m <sup>3</sup>
OES TWA [2]	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Ethyl Acetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

### 8.2. Monitoring methods

Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.
--------------------	--

### 8.3. Engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system.
----------------------------------	---

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves
Eye protection	: Wear eye protection: Chemical goggles or safety glasses
Skin and body protection	: Wear protective clothing: Long sleeved protective clothing. Wear foot protection
Respiratory protection	: Wear appropriate mask: Combined gas/dust mask with filter type

#### Personal protective equipment symbol(s)



Environmental exposure controls	: Avoid release to the environment.
Consumer exposure controls	: Personal protective equipment (PPE) is not required when handling individual retail pack.
Other information	: PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

### SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Various coloured aerosol with detectable odour.
Molecular mass	: Not applicable
Colour	: Various colours
Odour	: Not available
Odour threshold	: No data available
pH	: Not available
pH solution	: Not available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not available
Boiling point	: Not available
Flash point	: -80 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Flammability	: No data available
Vapour pressure	: Vapour pressure: Not available
Relative density	: Relative vapour density at 20°C: Not available. (Air=1).
Density	: Density: ≈ 0.8 kg/l Relative density: Not available. (Water = 1).
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: ≈ 10 cP
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: Not available
Fat solubility	: No data available

### SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg Source: ECHA
Ethyl Acetate (141-78-6)	
LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l

Skin corrosion/irritation	: Not classified pH: Not available
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not available

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

### Ethyl Acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)**

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

### Ethanol (64-17-5)

LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	--

NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
----------------------------	--

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)**

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

### Colour Code (Various Colours) - Aerosol Paints

Vaporizer	Aerosol
-----------	---------

Viscosity, kinematic	Not available
----------------------	---------------

### Ethanol (64-17-5)

Animal studies and expert judgment for classification	False
---	-------

Viscosity, kinematic	1.366 mm <sup>2</sup> /s
----------------------	--------------------------

### Ethyl Acetate (141-78-6)

Animal studies and expert judgment for classification	False
---	-------

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)**

Animal studies and expert judgment for classification	False
---	-------

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

Ethanol (64-17-5)	
LC50 - Fish [1]	> 100 mg/l Source: SIDS 2005
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
ErC50 algae	275 mg/l Source: ECHA
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC

Ethyl Acetate (141-78-6)	
EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Colour Code (Various Colours) - Aerosol Paints	
Partition coefficient n-octanol/water (Log Pow)	Not available

Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC

### 12.4. Mobility in soil

Colour Code (Various Colours) - Aerosol Paints	
Partition coefficient n-octanol/water (Log Pow)	Not available

Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

Colour Code (Various Colours) - Aerosol Paints	
Fluorinated greenhouse gases	False

Ethanol (64-17-5)	
Fluorinated greenhouse gases	False

Ethyl Acetate (141-78-6)	
Fluorinated greenhouse gases	False

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)**

Fluorinated greenhouse gases	False
------------------------------	-------

## SECTION 13: Disposal considerations




Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

### SECTION 14: Transport information

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344, 381  
Limited quantities (ADG) : See SP 277  
Excepted quantities (ADG) : E0  
Packing instructions (ADG) : P207, LP200  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW2  
Segregation (IMDG) : SG69

#### Air transport

UN-No. (IATA) : 1950  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802



# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

ERG code (IATA) : 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Listed

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

#### Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

Data sources : Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals  
Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals  
Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants  
Safe Work Australia - Hazardous Chemical Information System (HCIS)  
Australian Inventory of Industrial Chemicals (AICIS Inventory)  
Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020  
Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017  
Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017  
New Zealand - Chemical Classification and Information Database (CCID)  
New Zealand - Inventory of Chemicals (NZIoC)  
European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)  
European Chemicals Agency (ECHA) - REACH Study Results  
European Chemicals Agency (ECHA) - REACH Registration Dossiers  
United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)  
Uniform Scheduling of Medicines and Poisons (SUSMP)  
United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)  
Australian Dangerous Goods Code (ADG Code)  
International Air Transport Association Dangerous Goods Regulations (IATA DGR)  
International Maritime Dangerous Goods (IMDG Code).

Date of revision : 7/03/2023

Classification	
Aerosol 1	H222;H229
Eye Irrit. 2A	H319
STOT SE 3	H336
STOT RE 2	H373
Aquatic Acute 3	H402
Aquatic Chronic 3	H412

# Colour Code (Various Colours) - Aerosol Paints

## Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
Aerosol 1	Aerosol, Category 1
Aquatic Acute 2	Hazardous to the aquatic environment – Acute Hazard, Category 2
Aquatic Acute 3	Hazardous to the aquatic environment – Acute Hazard, Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation, Category 2B
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 3	Skin corrosion/irritation, Category 3
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H320	Causes eye irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.