

Safety Data Sheet

according to the WHS Regulations

Issue date: 7/08/2023 Supersedes: 7/08/2023 Version: 1.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture

Product name : Geo Vertical Spray - Red, Blue, Yellow, White

Product code : 11952 11953 11955 11956

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Application is by spray atomisation from a hand held aerosol pack.

Use according to manufacturer's directions.

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.4. Details of manufacturer or importer

Supplier

Signet Pty Ltd 56 Ingleston Rd WAKERLEY, QLD 4154

Australia

T +61 (07) 3179 2100

sales@signet.net.au - www.signet.net.au

1.5. Emergency phone number

Emergency number : Office hours: +61 (07) 3179 2100

Poisons Information Centre (24 h): 13 11 26

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2A H319
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)





Flame

: Danger

Exclamation

Signal word (GHS AU)

Contains : Ethyl Acetate (10 – 60 %); Acrylic Resin (10 – 30 %); Ethanol 100% (< 30 %); High Mol Wt

Wetting Agent (< 10 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Safety Data Sheet

according to the WHS Regulations

P103 - Read carefully and follow all instructions.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, protective clothing, protective gloves.

: AUH066 - Repeated exposure may cause skin dryness or cracking.

AUH044 - Risk of explosion if heated under confinement.

2.3. Other hazards which do not result in classification

No additional information available

Additional hazard statements (GHS AU)

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Ethyl Acetate	141-78-6	10 – 60
Acrylic Resin	-	10 – 30
Ethanol 100%	-	< 30
High Mol Wt Wetting Agent	-	< 10

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should

only be undertaken by skilled personnel. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness. Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Unsuitable extinguishing media : Unsuitable extinguishing media are not known.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

General measures : No action shall be taken without appropriate training or involving any personal risk. Notify

authorities if product enters sewers or public waters.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

7/08/2023 (Issue date) AU - en 2/10

Safety Data Sheet

according to the WHS Regulations

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire

remotely due to the risk of explosion.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Information on mixed storage : Store away from incompatible materials and products. Refer to the detailed list of

incompatible materials in section 10 Stability/Reactivity.

Storage area : Keep out of direct sunlight.

Special rules on packaging : Position containers so that any labeling information is visible. Keep packaging closed when

not in use. Check containers and packaging regularly for leaks and damage.

Packaging materials : Keep only in original packaging.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

7/08/2023 (Issue date) AU - en 3/10

Safety Data Sheet

according to the WHS Regulations

Ethyl Acetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Monitoring methods

Monitoring methods : Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable

gases/vapours may be released.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a

closed system.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment (PPE) must be suited to the nature of the work and any

hazard associated with the work as identified by the risk assessment conducted.

Avoid all unnecessary exposure. Ocular shower with suitable liquid.

Hand protection : Wear protective gloves

Eye protection : Wear eye protection: Chemical goggles or safety glasses
Skin and body protection : Wear protective clothing: Long sleeved protective clothing

Respiratory protection : Wear appropriate mask

Personal protective equipment symbol(s)











Consumer exposure controls

Other information

: Personal protective equipment (PPE) is not required when handling individual retail pack.

: PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance : Aerosol; not miscible with water.

Molecular mass : Not applicable
Colour : Various colours
Odour : Not available
Odour threshold : No data available
pH : Not applicable
pH solution : Not available
Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point: Not available

Boiling point : Not available

Flash point : -81 °C (hydrocarbon propellant).

Auto-ignition temperature : Not available

Decomposition temperature : Not available

Flammability : No data available

Vapour pressure : Vapour pressure: Not available

Relative density : Relative vapour density at 20°C: Not available. (Air=1).

Density : Density: ≈ 0.8 kg/l

Relative density: (Water = 1).

Solubility : Water: immiscible

7/08/2023 (Issue date) AU - en 4/10

Safety Data Sheet

according to the WHS Regulations

Partition coefficient n-octanol/water (Log Pow) : Not available Viscosity, kinematic : Not available Viscosity, dynamic : < 10 cP

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : No data available
Minimum ignition energy : No data available
VOC content : Not available
Fat solubility : No data available

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of

ignition.

Incompatible materials : Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethyl Acetate (141-78-6)	
LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l
High Mol Wt Wetting Agent	

LC50 Inhalation - Rat [ppm]	0 ppm
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h
LC50 Inhalation - Rat (Vapours)	> 20 mg/l/4h

Skin corrosion/irritation : Not classified

pH: Not applicable

Serious eye damage/irritation : Causes serious eye irritation.

pH: Not applicable

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

Ethyl Acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

Acrylic Resin STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

High Mol Wt Wetting Agent	
STOT-repeated exposure	May cause damage to organs (digestive tract) through prolonged or repeated exposure (oral).

Aspiration hazard : Not classified

Safety Data Sheet

according to the WHS Regulations

Geo Vertical Spray - Red, Blue, Yellow, White		
Vaporizer	Aerosol	
Viscosity, kinematic	Not available	
Ethyl Acetate (141-78-6)		
Animal studies and expert judgment for classification	False	
Acrylic Resin		
Animal studies and expert judgment for classification	False	
Viscosity, kinematic	1000 – 3000 mm²/s @ 25degC.	
High Mol Wt Wetting Agent		
Animal studies and expert judgment for classification	False	
Viscosity, kinematic	≈ 182 mm²/s	
Ethanol 100%		
Animal studies and expert judgment for classification	False	

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

 $\label{thm:local_equation} \mbox{Hazardous to the aquatic environment, short-term}$

cute)

: Not classified

≥ 4

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Ethyl Acetate (141-78-6)	
EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l
High Mol Wt Wetting Agent	
LOEC (acute)	1 – 10 mg/l
BCF - Other aquatic organisms [2]	≥ 500 mg/l

12.2. Persistence and degradability

Partition coefficient n-octanol/water (Log Kow)

No additional information available

12.3. Bioaccumulative potential

Geo Vertical Spray - Red, Blue, Yellow, White		
Partition coefficient n-octanol/water (Log Pow) Not available		
High Mol Wt Wetting Agent		
BCF - Other aquatic organisms [2]	≥ 500 mg/l	
Partition coefficient n-octanol/water (Log Kow) ≥ 4		

Safety Data Sheet

according to the WHS Regulations

12.4. Mobility in soil

Geo Vertical Spray - Red, Blue, Yellow, White		
Partition coefficient n-octanol/water (Log Pow) Not available		
High Mol Wt Wetting Agent		
Partition coefficient n-octanol/water (Log Kow) ≥ 4		

12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

Other adverse effects	No additional information available	
Geo Vertical Spray - Red, Blue, Yellow, White		
Fluorinated greenhouse gases	False	
Ethyl Acetate (141-78-6)		
Fluorinated greenhouse gases	False	
Acrylic Resin		
Fluorinated greenhouse gases	False	
High Mol Wt Wetting Agent		
Fluorinated greenhouse gases	False	
Ethanol 100%		
Fluorinated greenhouse gases	False	

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

ADG	IMDG	IATA		
14.1. UN number	14.1. UN number			
1950	1950	1950		
14.2. UN Proper Shipping Name				
AEROSOLS	AEROSOLS	Aerosols, flammable		
14.3. Transport hazard class(es)				
2.1	2.1	2.1		
2	2	2		
14.4. Packing group	14.4. Packing group			
Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No		

Safety Data Sheet

according to the WHS Regulations

14.6. Special precautions for user

Specific storage requirement : No data available Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344, 381

Limited quantities (ADG) : See SP 277

Excepted quantities (ADG) : E0

Packing instructions (ADG) : P207, LP200

Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

UN-No. (IATA) : 1950 PCA Excepted quantities (IATA) E0 Y203 PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) 30kgG 203 PCA packing instructions (IATA) 75kg PCA max net quantity (IATA) : 203 CAO packing instructions (IATA) CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : Listed

Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

7/08/2023 (Issue date) AU - en 8/10

Safety Data Sheet

according to the WHS Regulations

Data sources

: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous

Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants

Safe Work Australia - Hazardous Chemical Information System (HCIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory)

Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice

Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017

Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017

New Zealand - Chemical Classification and Information Database (CCID)

New Zealand - Inventory of Chemicals (NZIoC)

European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)

European Chemicals Agency (ECHA) - REACH Study Results

European Chemicals Agency (ECHA) - REACH Registration Dossiers

United Nations - Globally Harmonised System of Classification and Labelling of Chemicals

Uniform Scheduling of Medicines and Poisons (SUSMP)

United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)

Australian Dangerous Goods Code (ADG Code)

International Air Transport Association Dangerous Goods Regulations (IATA DGR)

International Maritime Dangerous Goods (IMDG Code).

Classification	
Aerosol 1	H222;H229
Eye Irrit. 2A	H319
Skin Sens. 1	H317
STOT SE 3	H336

Full text of H-statements	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation, Category 2B
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways

Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.