

Safety Data Sheet

according to the WHS Regulations Issue date: 14/02/2023 Version: 1.0

SECTION 1: Product identifier	
1.1. GHS Product identifier	
Product form Product name Product code	: Mixture : DO Ink- Green : 12185
1.2. Other means of identification	
Synonyms	: Ball Marking ink
1.3. Recommended use of the chemical a	nd restrictions on use
Recommended use Restrictions on use	 DO inks are a high viscosity permanent ink for marking almost any surface through ball markers. Not to be used for any purpose other than the one the product was designed for
1.4. Details of manufacturer or importer	
Supplier Signet Pty Ltd 56 Ingleston Rd WAKERLEY, QLD 4154 Australia T +61 (07) 3179 2100 sales@signet.net.au - www.signet.net.au	
1.5. Emergency phone number	
Emergency number	: Office hours: +61 (07) 3179 2100 Poisons Information Centre (24 h): 13 11 26

SECTION 2:	Hazard identification	

2.1. Classification of th	e hazardous chemical
---------------------------	----------------------

:

: Warning

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)

Flame	Exclamation mark	Health hazard

 ethylene glycol monobutyl ether (30 – 60 %)
 H226 - Flammable liquid and vapour H315 - Causes skin irritation H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

: P101 - If medical advice is needed, have product container or label at hand.

Signal word (GHS AU)	
Contains	
Hazard statements (GHS AU)	

Precautionary statements (GHS AU)

P102 - Keep out of reach of children.

Safety Data Sheet

according to the WHS Regulations

P103 - Read carefully and follow all instructions.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
ethylene glycol monobutyl ether	111-76-2	30 – 60
Ethanol	64-17-5	30 – 60

SECTION 4: First aid measures

4.1. Description of necessary first-aid	I measures
First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	 Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Symptoms caused by exposure	
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
4.3. Medical attention and special trea	atment
Other medical advice or treatment	: Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Unsuitable extinguishing media are not known.	
5.2. Specific hazards arising from the chemical		
Fire hazard General measures Hazardous decomposition products in case of fire	 Flammable liquid and vapour. No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters. Toxic fumes may be released. 	
5.3. Special protective equipment and precautions for fire-fighters		
Firefighting instructions Protection during firefighting	 Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 	

Safety Data Sheet

according to the WHS Regulations

Hazchem Code

: * 3Y

SECTION 6: Accidental release measures	
6.1. Personal precautions, protective e	equipment and emergency procedures
General measures	: No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and stor	age
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Information on mixed storage	 Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
Storage area	: Keep out of direct sunlight.
Special rules on packaging	: Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage.
Packaging materials	: Keep only in original packaging.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards Ethanol (64-17-5) Australia - Occupational Exposure Limits Local name Ethyl alcohol (Ethanol) OES TWA [1] 1880 mg/m³ OES TWA [2] 1000 ppm

Safety Data Sheet

according to the WHS Regulations

Pogulatory reference	Workplace expedite standards for sinhering contaminants (2010)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
ethylene glycol monobutyl ether (111-76-2)	
Australia - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl cellosolve; Butyl glycol; Ethylene glycol monobutyl ether; Glycol monobutyl ether)
OES TWA [1]	96.9 mg/m ³
OES TWA [2]	20 ppm
OES STEL	242 mg/m ³
OES STEL [ppm]	50 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
8.2. Monitoring methods	
Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.
8.3. Engineering controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment.
8.4. Individual protection measures, such as	s personal protective equipment (PPE)
Personal protective equipment	: Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves: Antistatic gloves
Eye protection Skin and body protection	 Wear eye protection: Chemical goggles or safety glasses Wear foot protection: antistatic boots. Wear protective clothing: Antistatic clothing, Flame
	retardant protective clothing
Respiratory protection	: Wear appropriate mask
Personal protective equipment symbol(s)	
Consumer exposure controls Other information	 Personal protective equipment (PPE) is not required when handling individual retail pack PPE compliant to the recommended standards should be selected. The following Austral and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industria Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

Physical state	: Liquid
Appearance	: No data available
Molecular mass	: Not applicable
Colour	: Green
Odour	: Not available
Odour threshold	: No data available
pH	: Not available
pH solution	: Not available

Safety Data Sheet

according to the WHS Regulations

Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not available
Boiling point	: 78 – 170 °C
Flash point	: 24 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Flammability	: No data available
Vapour pressure	: Vapour pressure: 1 – 5 kPa
Relative density	: Relative vapour density at 20°C: Not available. (Air=1).
Density	: Density: ≈ 0.9 kg/l
	Relative density: (Water = 1).
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: ≈ 1200 cP
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: Not available
Fat solubility	: No data available

SECTION 10: Stability and reactivi	ty
Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	 Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological informatio	n
Acute toxicity (oral) Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg Source: ECHA
ethylene glycol monobutyl ether (111-76-2)
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg Source: ECHA
Skin corrosion/irritation	: Causes skin irritation. pH: Not available
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not available
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Safety Data Sheet

according to the WHS Regulations

Ethanol (64-17-5)			
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:		
ethylene glycol monobutyl ether (111-76-2)			
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard :	Not classified		
DO Ink- Green			
Viscosity, kinematic	Not available		
Ethanol (64-17-5)			
Animal studies and expert judgment for classification	False		
Viscosity, kinematic	1.366 mm²/s		
ethylene glycol monobutyl ether (111-76-2)			
Animal studies and expert judgment for classification	False		

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

	0			4.1		14
1	2.1	L. F	- C C	ТО	XIC	ity
	_	_				

Hazardous to the aquatic environment, short–term : (acute)	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Not classified Not classified
Ethanol (64-17-5)	
LC50 - Fish [1]	> 100 mg/l Source: SIDS 2005
EC50 - Crustacea [1]	> 10000 mg/l Test organisms (species): Daphnia magna
ErC50 algae	275 mg/l Source: ECHA
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC
ethylene glycol monobutyl ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l Source: ECHA
EC50 - Crustacea [1]	1800 mg/l Source: ECHA
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA

12.2. Persistence and degradability

No additional information available

Safety Data Sheet

according to the WHS Regulations

Ethanol (64-17-5)			
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC		
ethylene glycol monobutyl ether (111-76-2)			
Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA		
12.4. Mobility in soil			
DO Ink- Green			
Partition coefficient n-octanol/water (Log Pow)	Not available		
Ethanol (64-17-5)			
Partition coefficient n-octanol/water (Log Pow)	-0.32 Source: ICSC		
ethylene glycol monobutyl ether (111-76-2)			
Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA		
12.5. Other adverse effects			
Ozone :	Not classified		
Other adverse effects :	No additional information available		
DO Ink- Green			
Fluorinated greenhouse gases	False		
Ethanol (64-17-5)			
Fluorinated greenhouse gases	False		
ethylene glycol monobutyl ether (111-76-2)			
Fluorinated greenhouse gases	False		

SECTION 13: Disposal considerations

Waste treatment methods Additional information

Dispose of contents/container in accordance with licensed collector's sorting instructions.Flammable vapours may accumulate in the container.

ADG	IMDG	ΙΑΤΑ
4.1. UN number		
1210	1210	1210
14.2. UN Proper Shipping Name		
PRINTING INK	PRINTING INK	Printing ink
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III - Substances presenting low danger	III	

Safety Data Sheet

according to the WHS Regulations

ADG	IMDG	ΙΑΤΑ			
14.5. Environmental hazards					
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No			
14.6. Special precautions for user					
Specific storage requirement	: No data available				
Shock sensitivity	: No data available				
14.7. Additional information					
Other information : No supplementary information available					
Transport by road and rail					
UN-No. (ADG)	: 1210				
Special provision (ADG)	: 163, 223, 367				
Limited quantities (ADG)	: 51				
Excepted quantities (ADG)	: E1				
Packing instructions (ADG)	: P001, IBC03, LP01				
Special packing provisions (ADG) Portable tank and bulk container instructions (ADG)	: PP1				
Portable tank and bulk container instructions (ADG)					
(ADG)	. 161				
Transport by sea					
UN-No. (IMDG)	: 1210				
Special provisions (IMDG)	: 163, 223, 367, 955				
Limited quantities (IMDG)	: 5 L				
Excepted quantities (IMDG)	: E1				
Packing instructions (IMDG)	: P001, LP01				
Special packing provisions (IMDG)	: PP1				
IBC packing instructions (IMDG)	: IBC03				
Tank instructions (IMDG)	: T2 : TP1				
Tank special provisions (IMDG)	: F-E - FIRE SCHEDULE Echo - NON-WATE				
EmS-No. (Fire) EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAM				
Stowage category (IMDG)	: A				
Properties and observations (IMDG)		matter in solution or suspension. Miscibility with			
	water depends upon the solvent.	matter in solution of suspension. Miscipling with			
Air transport					
UN-No. (IATA)	: 1210				
PCA Excepted quantities (IATA)	: E1				
PCA Limited quantities (IATA)	: Y344				
PCA limited quantity max net quantity (IATA)	: 10L				
PCA packing instructions (IATA)	: 355				
PCA max net quantity (IATA) CAO packing instructions (IATA)	: 60L : 366				
CAO packing instructions (IATA) CAO max net quantity (IATA)	220L				
Special provisions (IATA)	. 220L : A3, A72, A192				
ERG code (IATA)	: A3, A72, A192 : 3L				
14.8. Hazchem or Emergency Action Code					
Hazchem Code	: * 3Y				

Safety Data Sheet

according to the WHS Regulations

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : Listed Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

Data sources

: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants Safe Work Australia - Hazardous Chemical Information System (HCIS) Australian Inventory of Industrial Chemicals (AICIS Inventory) Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020 Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017 Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017 New Zealand - Chemical Classification and Information Database (CCID) New Zealand - Inventory of Chemicals (NZIoC) European Chemicals Agency (ECHA) - Annex VI (C&L Inventory) European Chemicals Agency (ECHA) - REACH Study Results European Chemicals Agency (ECHA) - REACH Registration Dossiers United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS) Uniform Scheduling of Medicines and Poisons (SUSMP) United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation) Australian Dangerous Goods Code (ADG Code) International Air Transport Association Dangerous Goods Regulations (IATA DGR) International Maritime Dangerous Goods (IMDG Code).

Classification	
Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
STOT RE 2	H373

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. 5 (Dermal)	Acute toxicity (dermal), Category 5

Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Liq. 4	Flammable liquids, Category 4
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H302	Harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.