

Safety Data Sheet

according to the WHS Regulations

Issue date: 11/01/2023 Date of revision: 31/01/2023 Supersedes: 11/01/2023 Version: 1.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product name : Metallic Silver Zinc

Product code 14204

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use Primer / Finish

Restrictions on use Not to be used for any purpose other than the one the product was designed for

1.4. Details of manufacturer or importer

Supplier

Signet Pty Ltd 56 Ingleston Rd WAKERLEY, QLD 4154 Australia

T+61 (07) 3179 2100

sales@signet.net.au - www.signet.net.au

1.5. Emergency phone number

: Office hours: +61 (07) 3179 2100 **Emergency number**

Poisons Information Centre (24 h): 13 11 26

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

H222;H229 Aerosol, Category 1

Substances and Mixtures which, in contact with water, emit flammable H261

gases, Category 2

Serious eye damage/eye irritation, Category 2A H319 Specific target organ toxicity - Single exposure, Category 3, Narcosis H336 Specific target organ toxicity - Repeated exposure, Category 2 H373 Hazardous to the aquatic environment - Acute Hazard, Category 3 H402

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)







Flame

Exclamation Health hazard

mark

Signal word (GHS AU) : Danger

Ethyl Acetate (30 - 60 %); Butyl Acetate (< 10 %); Naphtha (petroleum), hydrodesulfurized Contains

heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (< 10 %); Solvent naphtha (petroleum), light aromatic [contains less than 0,1 % w/w benzene] (< 10 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

31/01/2023 (Date of revision) AU - en 1/10

Safety Data Sheet

according to the WHS Regulations

H261 - In contact with water releases flammable gases

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H402 - Harmful to aquatic life

Precautionary statements (GHS AU) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read carefully and follow all instructions.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P223 - Do not allow contact with water.

P231+P232 - Handle and store contents under inert gas. Protect from moisture.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Ethyl Acetate	141-78-6	30 – 60
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).]	64742-82-1	< 10
Aluminium powder (stabilised)	7429-90-5	< 10

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. Wash skin

with plenty of water.

First-aid measures after eye contact : Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should

only be undertaken by skilled personnel. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Unsuitable extinguishing media are not known.

31/01/2023 (Date of revision) AU - en 2/10

Safety Data Sheet

according to the WHS Regulations

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

General measures : No action shall be taken without appropriate training or involving any personal risk. Notify

authorities if product enters sewers or public waters.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Thermal decomposition can lead to the release of irritating

gases and vapours.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance

and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No action shall be taken without appropriate training or involving any personal risk. Notify

authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Handle under inert gas. Protect from moisture.

Do not allow contact with water. Do not breathe dust/fume/gas/mist/vapours/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Protect from moisture. Store in a dry place. Store in a closed container. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in

a well-ventilated place. Keep container tightly closed. Keep cool.

Information on mixed storage : Store away from incompatible materials and products. Refer to the detailed list of

incompatible materials in section 10 Stability/Reactivity.

Storage area : Keep out of direct sunlight.

Special rules on packaging : Position containers so that any labeling information is visible. Keep packaging closed when

not in use. Check containers and packaging regularly for leaks and damage.

31/01/2023 (Date of revision) AU - en 3/10

Safety Data Sheet

according to the WHS Regulations

Packaging materials : Keep only in original packaging.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethyl Acototo (144 79 6)		
Ethyl Acetate (141-78-6)		
Australia - Occupational Exposure Limits		
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
Aluminium powder (stabilised) (7429-90-5)		
Australia - Occupational Exposure Limits		
Local name	Aluminium	
OES TWA [1]	10 mg/m³ metal dust 5 mg/m³ welding fumes (as Al) 2 mg/m³ alkyls (NOC) (as Al) 5 mg/m³ pyro powders (as Al) 2 mg/m³ soluble salts (as Al)	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	

8.2. Monitoring methods

Monitoring methods

: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.

8.3. Engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system. Handle under inert gas. Protect from moisture.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment

 Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.
 Avoid all unnecessary exposure. Ocular shower with suitable liquid.

Hand protection

: Wear protective gloves

Skin and body protection

: Wear protective clothing: Long sleeved protective clothing. Wear foot protection. Use protective apron: Chemical resistant apron

Respiratory protection

: Wear a self contained breathing apparatus

Personal protective equipment symbol(s)













Environmental exposure controls Consumer exposure controls

Other information

- : Avoid release to the environment.
- : Personal protective equipment (PPE) is not required when handling individual retail pack.
- PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state : Liquid

31/01/2023 (Date of revision) AU - en 4/10

Safety Data Sheet

according to the WHS Regulations

Appearance : Paint in aerosol can.

Colour : Metallic Odour : Solvent

Odour threshold : No data available pH : No data available pH solution : No data available Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point: Not applicable

Boiling point No data available No data available Flash point Auto-ignition temperature No data available : No data available Flammability : No data available Vapour pressure Relative density : No data available Density : Density: ≈ 0.776 kg/l Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : No data available
Minimum ignition energy : No data available
Fat solubility : No data available

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use. In contact with water

releases flammable gases.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of

ignition. Water, humidity.

Incompatible materials : Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Ethyl Acetate (141-78-6)	
LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l

	o milataren 1 tat (2 aetimet)	e. ree mg.
Aluminium powder (stabilised) (7429-90-5)		
LD50	0 oral rat	> 15900 mg/kg Source: ECHA
LC50	0 Inhalation - Rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
LC50	0 Inhalation - Rat (Dust/Mist)	> 0.888 mg/l Source: ECHA

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

Safety Data Sheet

according to the WHS Regulations

Ethyl Acetate (141-78-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure :	May cause damage to organs through prolonged or repeated exposure.	
Aluminium powder (stabilised) (7429-90-5)		
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)	
NOAEL (subchronic, oral, animal/male, 90 days)	1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)	
NOAEL (subchronic, oral, animal/female, 90 days)	1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)	
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)		
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard :	Not classified	
Metallic Silver Zinc		
Vaporizer	Aerosol	
Ethyl Acetate (141-78-6)		
Animal studies and expert judgment for classification	False	
Aluminium powder (stabilised) (7429-90-5)		
Animal studies and expert judgment for classification	False	
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)		
Animal studies and expert judgment for classification	False	

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Harmful to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Ethyl Acetate (141-78-6)	
EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l

Safety Data Sheet

according to the WHS Regulations

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

Metallic Silver Zinc

Fluorinated greenhouse gases False

Ethyl Acetate (141-78-6)

Fluorinated greenhouse gases False

Aluminium powder (stabilised) (7429-90-5)

Fluorinated greenhouse gases False

Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)

Fluorinated greenhouse gases False

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

ADG	IMDG	IATA	
14.1. UN number			
1950	1950	1950	
14.2. UN Proper Shipping Name			
AEROSOLS	AEROSOLS	Aerosols, flammable	
14.3. Transport hazard class(es)			
2.1	2.1	2.1	
2	2	2	
14.4. Packing group			
Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	

Safety Data Sheet

according to the WHS Regulations

14.6. Special precautions for user

Specific storage requirement : No data available Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344, 381

Limited quantities (ADG) : See SP 277

Excepted quantities (ADG) : E0

Packing instructions (ADG) : P207, LP200

Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

: 1950 UN-No. (IATA) PCA Excepted quantities (IATA) E0 Y203 PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) 30kgG 203 PCA packing instructions (IATA) 75kg PCA max net quantity (IATA) 203 CAO packing instructions (IATA) CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All the chemicals contained in this product are listed introductions

Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Unscheduled

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Update of the SDS from former GHS version to the 7th edition of the GHS (GHS 7).

31/01/2023 (Date of revision) AU - en 8/10

Safety Data Sheet

according to the WHS Regulations

Data sources : Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous

Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals

Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants

Safe Work Australia - Hazardous Chemical Information System (HCIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory)

Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020

Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017

Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017

New Zealand - Chemical Classification and Information Database (CCID)

New Zealand - Inventory of Chemicals (NZIoC)

European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)
European Chemicals Agency (ECHA) - REACH Study Results

European Chemicals Agency (ECHA) - REACH Registration Dossiers

United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)

Uniform Scheduling of Medicines and Poisons (SUSMP)

United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)

Australian Dangerous Goods Code (ADG Code)

International Air Transport Association Dangerous Goods Regulations (IATA DGR)

International Maritime Dangerous Goods (IMDG Code).

: 31/01/2023

Date of revision

Classification	
Aerosol 1	H222;H229
Water-react. 2	H261
Eye Irrit. 2A	H319
STOT SE 3	H336
STOT RE 2	H373
Aquatic Acute 3	H402

Full text of H-statements	
Aerosol 1	Aerosol, Category 1
Aquatic Acute 2	Hazardous to the aquatic environment – Acute Hazard, Category 2
Aquatic Acute 3	Hazardous to the aquatic environment – Acute Hazard, Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation, Category 2B
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Skin Irrit. 3	Skin corrosion/irritation, Category 3
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2

Safety Data Sheet

according to the WHS Regulations

Full text of H-statements	
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H228	Flammable solid
H261	In contact with water releases flammable gases
H304	May be fatal if swallowed and enters airways
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H320	Causes eye irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.