



Metallic Silver Zinc Spray - 350g

PRIMER & TOPCOAT

- · Provides a Metallic Silver Finish
- · Made in Australia
- Rust Preventative Topcoat Spray suitable for a variety of services including Steel, Galvanised Steel, Sheet Metal and Structural Steel.
- Product Size: 350g
- Drying Time | Hard Dry = 30 minutes, Touch Dry = 5 minutes
- For best results, we recommend using this item as a topcoat over our Premium Zinc Spray (Item No. #14216) or Zinc Shield Spray (Item No. #14202).



DIRECTIONS FOR USE

Signet Pty LtdPO Box 767 Capalaba DC QLD 4157



signet.net.au



13 7446



Metallic Silver Zinc Spray - 350g

PRIMER & TOPCOAT

Signet's Own Metallic Silver Zinc Spray is manufactured in Australia on our premises, which allows Signet to continually perform quality testing to ensure it is up to our highest standard. Metallic Silver Zinc Spray protects metal surfaces such as Steel, Galvanised Iron, Sheet metal and Structural Steel from corrosion. Providing an additional layer of protection and a durable metallic silver finish, for optimal results we recommend applying our Metallic Silver Zinc Spray over our Premium Zinc Spray (Item No. #14216) or Zinc Shield Spray (Item No. #14202) as a topcoat.

Surface Preparation

Remove all rust and flaking paint back to bare metal with a wire brush, scraper or mechanical sander. Remove grease, oil and other contaminants. Sand new metal and any existing coatings thoroughly and remove all dust with a dry brush or vacuum.

Application

Shake can vigorously for one 30 seconds after the mixing ball begins to rattle. if mixing ball fails to rattle DO NOT STRIKE CAN. Shake often during use. Hold can upright 15-20cm from surface and spray in a steady back-and-forth motion, applying a mist coat followed by a full even coat, slightly overlapping each stroke. Avoid spraying too close to the surface or spraying too heavily, this will prevent sagging and give a smooth, even finish. Do not use near open flame. After use, clean valve immediately by turning the can upside down and depressing spray button for 2 seconds until only gas escapes. Overspray can be removed with acetone.

Ideal Application Temperature

Between 10*C and 32*C.

For Best Results

Ideal for coating metal surfaces including steel and galvanized steel structures and equipment, tank exteriors, wrought iron and more. We recommend using this item as a topcoat over our Premium Zinc Spray (Item No. #14216) or Zinc Shield Spray (Item No. #14202)



Item 14216 (Premium Zinc)
Item 14204 (Metallic Silver)
Item 14202 (Zinc Shield)
Item 14217 (1L Zinc Paint)



SAFETY INFORMATION

Signet Pty Ltd PO Box 767 Capalaba DC QLD 4157



signet.net.au



3 13 7446



Metallic Silver Zinc Spray - 350g

PRIMER & TOPCOAT

First Aid & Safety Information

Please refer to product SAFETY DATA SHEET (SDS) before use. Safety data sheets are available for download on individual product pages, visit signet.net.au

SAFETY

KEEP OUT OF REACH OF CHILDREN.

If swallowed, seek medical advice immediately and show the container or label. Do not induce vomiting. If in eyes, immediately flush with running water for at least 15 minutes. Seek immediate medical attention. Avoid breathing in vapor or mist. Use only with adequate ventilation. If on skin, remove contaminated clothing and wash skin thoroughly with soap and water. WARNING - Misuse by concentrating and inhaling contents can be harmful or fatal.

For 24-hour medical emergency response in Australia call 131126 and in New Zealand call 0800 764 766.

CAUTION

HIGHLY FLAMMABLE. KEEP AWAY FROM FLAME AND ELIMINATE ANY SOURCE OF IGNITION. Keep in a cool place and out of sun. Contents under pressure. Do not puncture or incinerate this can, even when empty.

ENVIRONMENT

Residual paint should be sprayed onto newspaper, allowed to dry and then dispose of via domestic waste collections. Empty aerosol cans are recyclable via can recycling programs.



