





Temporary Spot Marking Chalk Spray

AEROSOL SPRAY – 350g

- High visibility, temporary ground marking spray.
- Ideal for utility location and surveyors.
- Chalk can be washed away when marking is no longer required.
- Trigger cap for inverted, safe marking.
- **Coverage** | Will produce 300+ 'X' marks, 200+ metres continuous spray, 8–10sqm per can.
- **Suitable Surfaces** | Concrete, bitumen, steel, timber and general ground surfaces. Can be removed with water and stiff brush.
- **Drying Time** | 1–2 minutes.



-  Item 41805 [Yellow]
-  Item 41806 [White]

Other colours available, enquires call **13 7446**.
Please note: Printed colours are indicative only.



1 Apply Spot Marking Chalk Spray to desired area.



2 To remove, scrub off using water and a stiff bristled brush.



3 After scrubbing, surface is returned to original condition.

DIRECTIONS FOR USE

Signet Pty Ltd

PO Box 767 Capalaba DC QLD 4157

 signet.net.au

 13 7446



Temporary Spot Marking Chalk Spray

AEROSOL SPRAY – 350g

A high visibility, quick-dry ground marking spray suitable for TEMPORARY marking on concrete, bitumen, steel, timber and general ground surfaces. Ideal for use in public areas where permanent marks are not required. Semi-permanent marking that can be removed with water and stiff brush. Temporary Spot Marking Chalk Spray is suitable for use with Signet's Own 2-Wheel Spotting Handle or Aluminium Backsaver Spotting Handle.

Ideal Application Temperature

Between 10°C and 40°C.

Before Spraying

Shake can for at least 30 seconds after the mixing ball begins to rattle. Shake can occasionally during use.

Application

Hold can in the INVERTED or upside-down position approximately 10–15cm from the surface. The width of spray can be adjusted by moving closer to or further from the surface. It is best to avoid use in windy conditions which can impact application effectiveness. Drying time can be slower in cold and humid conditions or where heavy paint coating is applied.

Clean Up

After use, prevent blocking by holding the can UPRIGHT and spraying until only clear gas escapes. Wipe clean the spray tip nozzle.

Removal

Temporary Spot Marking Chalk Spray can be removed with the use of water and a stiff brush. NB: Removal may be hindered on fresh bitumen or other porous surfaces, removal may be hampered due to solvent/pigment penetration.

First Aid & Safety Information

Please refer to product SAFETY DATA SHEET (SDS) before use.

Safety data sheets are available for download on individual product pages, visit signet.net.au.

